


### 技术要求

1. 塑件表面应光洁, 无毛刺, 明显收缩, 缺陷, 裂纹等现象;
2. 插针表面电镀应光亮, 无斑纹, 划痕;
3. 未注公差按SJ1372-79中7级;
4. 温度范围: -25℃ 85℃;
5. 额定电压: 250V, AC, DC;
6. 接触电阻:  $\leq 0.01 \Omega$ ;
7. 绝缘电阻:  $\geq 1000m\Omega$ ;
8. 耐压: 1500V, AC/minute

UNITS mm		<b>mstconn</b> 深圳市德瑞电子有限公司 SHENZHEN DERUI ELECTRONIC CO., LTD.							
MAT'L		PART NO.(INTENDED USE) BH3. 5-2PK	TITLE: 3. 5-2P高压插座带扣						
FINISH		APPD:	DWG NO.: BH3. 5-2P带扣						
Q'TY PCS		CHKD:	 <table border="1"> <tr> <td>SCALE</td> <td>SHEET</td> <td>REV.</td> </tr> <tr> <td>1/1</td> <td>1/1</td> <td>A</td> </tr> </table>	SCALE	SHEET	REV.	1/1	1/1	A
SCALE	SHEET	REV.							
1/1	1/1	A							
X.± 0.3	X°.± 5°	DR: HU 2016. 09. 28							
.X± 0.25	.X°.± 2°								
.XX± 0.20	.XX°.± 1°								
.XXX± 0.10	.XXX°.± 0.5°								