


RECOMMENDED PCB LAYOUT

特性: Specifications:
电器: Electrical:

- 接触阻抗: Contact Resistance 50 milliohms MAX
- 耐电压: Dielectric Withstanding Voltage: 100 V AC AT Sea Level
- 绝缘阻抗: Insulation Resistance: 100 MEGA ohms MIN

材料: Material:

- 塑胶: Housing: High Temperature Thermoplastics, UL 94V-0 耐高温塑胶
- 端子: Contact: Copper Alloy 铜合金
- 铁壳: Shell: Copper Alloy 铜合金
- 电镀: Finish: 电镀点镀金: 脚镀锡
- 端子: Contact: Plated Gold in Mating Area; Tin On Solder Tails
- 铁壳: Shell: Nickel/ Plating 镀镍



UNITS	mm
MATL	FINISH
X ± 0.3	X ± 5°
X ± 0.25	X ± 2°
XX ± 0.20	XX ± 1°
XXX ± 0.10	XXX ± 0.5°
QTY	PCS

mstconn		PART NO.(INTENDED USE) MINI-USB-90°-2B	
APPD:		TITLE: MINI USB B-TYPE 5P 90度 母座两脚插板	
CHKD:		DWG NO.: A004-2B-7D	
DR: HU 2016.09.28		SCALE	SHEET
		1/1	1/1
		REV.	A

深圳市德瑞电子有限公司
SHENZHEN DERUI ELECTRONIC CO., LTD.