



特性: Specifications:
电器: Electrical:

1. 接触阻抗: Contact Resistance
30 milliohms MAX
2. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
3. 绝缘阻抗: Insulation Resistance:
1000MEGA ohms MIN

机构: Mechanical:

1. 结合力: Mating Force:
4.0KG MAX 最大4kg
2. 拔出力: Umating Force:
0.7 KG MIN 最少0.7kg

材料: Material:

1. 塑胶: Housing: Hing Temperature Thermoplasti
U1 94V-0 耐高温塑胶
2. 端子: Contact: Copper Alloy 铜合金
3. 铁壳: Shell: Copper Alloy 铁/铜合金

- 电镀: Finish:
- 1 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Tails
接触点镀金. 脚镀锡
 2. 铁壳: Shell:
Nickel Plating 镀镍

mstcom

深圳市德瑞电子有限公司
SHENZHEN DERUI ELECTRONIC CO., LTD.



成品图

品名	USB A TYPE 加后盖 90度 母座	材质		单位	MM
图号	CP-U8001-1D	图纸编号		比例	1:1
制图		审核		日期	2005.11.03