


RECOMMENDED PCB LAYOUT



SECTION A-A

特性: Specifications:
 电器: Electrical:
 接触阻抗: Contact Resistance
 50 milliohms MAX

耐压: Dielectric Withstanding Voltage:
 100 V AC AT Sea Level

绝缘阻抗: Insulation Resistance:
 100 MEGA ohms MIN

材料: Material:
 塑胶: Housing: High Temperature Thermoplastics,
 UL 94V-0 耐高温塑胶

端子: Contact: Copper Alloy 铜合金

铁壳: Shell: Copper Alloy 铜合金

电镀: Finish:
 端子: Contact: Plated Gold in Mating Area;
 Tin On Solder Tails

接触点镀金. 脚镀锡

铁壳: Shell:
 Nickel/ Plating 镀镍

UNITS mm		PART NO.(INTENDED USE) mstconn MINI USB 5P		TITLE: MINI USB B-TYPE 5P SMT 母座 (0.31)	
MATL		APPD:		DWG NO.: A036	
FINISH		CHKD:		SCALE	
X± 0.3	X± 5'	DR: HU 2016.09.28		SHEET	
X± 0.25	X± 2'			1/1	
XXX± 0.20	XX± 1'			REV.	
XXX± 0.10	XXX± 0.5'			A	
QTY		PCS			

A 1 2 3 4 5 6 7 8 9

F E D C B A