


P.C.B LAYOUT  
(TOLERANCE:±0.05)

- NOTES:
- 1.MATERIAL:  
HOUSING: HIGH TEMPERATURE THERMOPLASTIC  
UL94V\_0,COLOR:BLACK.  
CONTACT: COPPER ALLOYS,  
COVER: COPPER ALLOYS OR STEEL.
  - 2.PLATING:  
UNDERPLATE: NICKEL.  
CONTACT AREA: GOLD OVER NICKEL.  
SOLDER AREA: TIN OVER NICKEL.
  - 3.MULTIMEDIA CARD COMPATIBLE

PIN NO.	NAME	TYPE	DESCRIPTION
1	DATE	I/O/PP	DATE LINE(BIT2)
2	CD/DATE3	I/O/PP	CARD DETECT DATE LIN(BIT3)
3	CMD	PP	COMMAND RESPONSE
4	VDD	S	SUPPLY VOLTAGE
5	CLK	I	CLOCK
6	VSS	S	SUPPLY VOLTAGE GROUND
7	DATE	I/O/PP	DATE LINE(BIT0)
8	DATE	I/O/PP	DATE LINE(DIT1)



UNITS	MAT'L	FINISH	Q'TY
mm			PCS
X± 0.3		X± 5'	
X± 0.25		X± 2'	
XX± 0.20		XX± 1'	
XXX± 0.10		XXX± 0.5'	

**mstconn** 深圳市德瑞电子有限公司  
SHENZHEN DERUI ELECTRONIC CO., LTD.

PART NO.(INTENDED USE)  
TP-PUSH CARD双压片

TITLE:  
TP-TP自弹带双压片-1

DWG NO.:  
TFWF6-EBS1-1101

SCALE: 1/1 SHEET: 1/1 REV: A

DR: HU 2016.09.28