

深圳市德瑞电子有限公司

样品图规

CUSTOMER (客户):

Customer Part NO. (客户部品号):

Part Description (部品规格): 0.5*41*500*B(3/3*13/13)*(0.035*0.3裸铜)

Item	项目	Specification	规格值
NO. of conductors	导体芯数 N	41	
Pitch	间距 P	0.5±0.05	
Total Pitch	全间距 PT	20±0.05	
Total Length	总长度 L	500±3	
Insulation Length	绝缘长度 IL	494±3	
Margin Width	边缘宽度 M	2±0.05	
Total Width	总宽度 W	24±0.05	
Strip Length	线口长度 S1	3±1	
Strip Length	线口长度 S2	3±1	
Reinforeing tape length	补强板长度 B1	13±1	
Reinforeing tape length	补强板长度 B2	13±1	
Slanting	线口倾斜度 A	≤0.3	
Over lap	冲孔	/	
Terminal thickness	插入厚度 t1	0.32±0.05	
Thickness insulation	线身厚度 t	0.155±0.02	
Conductor thickness	导体厚度 Ct	0.035±0.005	裸铜
Conductor width	导体宽度 Cw	0.3±0.03	
Supporting Tape Color	补强板颜色	蓝色(Blue)	
PET (Supporting Tape Color)	补强板规格	0.225mm	
PET (Insulation)	绝缘胶规格	0.06mm 印字	
PET (Insulation)	绝缘胶规格	0.06mm 白色	
Rev	版本	A	

印字面
AWM 20706 105C 60V VW-1
0.665
印字面
IL
0.25mm锡箔材
0.25mm锡箔材
t1
B1
B2
t
Ct
Cw
S1
S2
PT

印字面
AWM 20706 105C 60V VW-1
A

两面居中贴22宽X486长锡箔材

Storage condition (储存条件): Recommended (推荐)
Temp: 15° C~25° C (温度 15° C~25° C) Humidity: 30~60RH% (湿度 30~60RH%)

Drawing Not To Scale
Hidden Lines Not Shown
图规不能以其线材比便来衡量, 隐藏线不显示。

Unit(单位):mm

Discharge Date
2017-11-25

Drawing by
Ling

Review Date
2017-11-25

Checked by
Ling

Drawing NO
图纸编号

Approved by
确认